


Specification Data Sheet

Rev 1.1 December 2014

Armour Home Electronics R&D Department



The Systemline 7 Netamp is a two zone stereo smart IP controllable audio amplifier designed specifically for the installation industry. The attachable side brackets allow it to mount to a wall or cabinet, the front fixings allow it to mount to a Systemline Homenet cabinet. It can be used with analogue or digital sources via its general inputs, or with the Systemline NetServer via its digital USB sockets. It contains integrated amplification for both zones, high quality DAC's and pre-amp stages for the best sound quality. It also contains sockets for local zone inputs and local keypad control.

Audio inputs

Analogue / digital inputs	3 x Combined analogue / optical digital	3.5mm jack / mini Toslink
Digital inputs	2 x USB	16bit 44kHz USB B Type
	2 x Local digital SPDIF	RJ45

Audio outputs

Speaker outputs	4 x Speaker 25W/ch at 8Ω	IMO (stereo per zone)
Line outputs	4 x Line outputs fixed or variable	Phono (stereo per zone)

Control





Triggers	2 x 12V triggers	3.5mm jack (one per zone)
Ethernet	1 x Local Area Network ethernet	RJ45
Keypads	2 x Local keypad control (for KPS-3 or KPS-11)	RJ45 (one per zone)

Amplifier

Type	Class D	
Continuous output power	25W/ch into 8Ω	45W/ch into 4Ω
Rated total harmonic distortion	<0.1%	
Frequency response	20Hz - 22kHz ±3dB	
Noise	-80dBV (20Hz - 22kHz A-weighted)	

General

Power	110 - 240V AC	Fig 8 mains socket
Standby power	<0.5W	
Dimensions	Height: 190mm, Width: 180mm, Depth: 89mm	
Net Weight	2.2kg	



*All measurements in mm

**Grey dimensions apply when product is fitted with wall brackets